

Dostępne konfiguracje Lasera CO2 Artemis RB

configurat ion	Basic	Standard	Premium	Deluxe
work area	900x600	900x600	1300x900	1300x900
Z-axis Lifting	200mm	200mm	200mm	200mm
laser source	CO2 Glass T2 100W	CO2 RF 60W	CO2 Glass T4 130W	CO2 RF 60W
Laser adjustable power	1-100%	1-100%	1-100%	1-100%
Autofocus	Yes	Yes	Yes	Yes
CCD vision	Yes	Yes	Yes	Yes
OPTICS	Focus lensed, Mirror	Focus lensed, Mirror	Focus lensed, Mirror	Focus lensed, Mirror
All-in-one Water-cooling	CW5200	CW5200	CW5200	CW5200
Moter	Setpper Moter	Full-servo Moter	Setpper Moter	Full-servo Moter
Software	Ruidawork lightburn	Ruidawork lightburn	Ruidawork lightburn	Ruidawork lightburn
Power	AC220V/50 Hz	AC220V/50H z	AC220V/50H z	AC220V/50H z
Security Configuration	key switch, emergency stop, switch Open cover protection	key switch, emergency stop, switch Open cover protection	key switch, emergency stop, switch Open cover protection	key switch, emergency stop, switch Open cover protection